SECURE ROOF COMPONENTS™
by Eagle Roofing Products

SECURE GUARD 60™

Robust. Reliable. Resilient.

In partnership with our friends at G.A.P. Roofing, Inc., Secure Guard 60 is a polyester-reinforced, non-woven surfaced underlayment designed for steep slope tile and metal applications.

Equipped with incredible durability and strength, Secure Guard 60 delivers excellent bonding and material fortitude while protecting homes and commercial buildings from extreme weather conditions like blazing heat, torrential rains, powerful winds and beyond.

The optimal choice for a formidable, cost-effective solution, Secure Guard 60 features a:

- strong 60 mil material that seals better around screws and holds up to traffic
- split release film for quick and seamless application
- roll size that covers 2 squares of roof area
- plastic wrap for minimal trash at job sites
- 30 Year Limited Warranty provided by G.A.P
- 180-day UV exposure period

In addition, it:

- is suited for Concrete Tile Roofs, Clay Tile Roofs, as well as Mechanically Fastened Roof Systems
- is listed as an approved underlayment by most tile foam adhesive manufacturers for Tile Roof Adhesive Systems
- is temperature resistant to 265°F, making it ideal for Metal Roofing Systems
- is designed to be an air, water and vapor barrier
- is an ideal product to use on critical roof areas
- is ASTM E108 Tested: Class A Assembly under Eagle Concrete Roof Tiles
- is made in North America adhering to U.S. standards using safe components





Choose peace of mind with a dependable shield that provides complete protection against the elements.

connect with us!

eagleroofing.com

EAGLE® ROOFING PRODUCTS

SECURE ROOF COMPONENTS™
by Eagle Roofing Products

SECURE GUARD 60™

Forge Resilient Roofs with an Underlayment You Can Rely On

Crafted for high temperature applications under adhesive-bonded tile roofs as well as metal and mechanically attached systems, Secure Guard 60* is an outstanding underlayment that provides utmost protection from ice, rain, wind and fire. Manufactured to last, Secure Guard 60 is easy to install while remaining remarkably strong and enduring.





Technical Description Provided by G.A.P.

Material Performance	ASTM Method	Results
Maximum Load MD/CD min	D2523/D1970	≥ 25 lbf/in
Elongation at Break	D2523/D1970	≥ 10%
Adhesion to Plywood, min @ 40°F	D903/1970	≥ 2.0 lbf/ft
Adhesion to Plywood, min @ 75°F	D903/D1970	≥ 12.0 lbf/ft
Low Temperature Flexibility, max	D1970	Pass
Tear Resistnace MD/CD, min	D4073/D1970	≥ 20 lbf
Moisture Vapor Permeance	E96	≥ 0.1 U.S. perms
Sealability Around Nail	D1970/D7349	Pass
Waterproof Integrity After Low-Temp Flexibility	D1970	Pass
Waterproof Integrity of Lap Seam	D1970/D7349	Pass

Data

ASTM Specification D1970		Applicable Standards
Rolls per Pallet	25	ASTM 1970
Wt/Roll	Approx. 68 lbs (nom)	ASTM E108
Roll Size	39 3/8" x66'	Florida Building Code
Thickness	60 mils	Miami-Dade Approved
Coverage	2 Square	Texas Department of Insurance

For more information and to register the 30 Year Limited Warranty associated with Secure Guard 60 by G.A.P. Roofing, Inc., visit: eagleroofing.com/secure-guard-60

**Secure Guard 60 is a product of Eagle Roofing Products "Secure Roof Components" line.*